



**PUMA  
POLYMERS**  
**MASTERWORKS™**  
**PIGMENT PASTES**

PRODUCT BULLETIN

### INTRODUCTION

Master Works™ pigment pastes are a range of water based pigment dispersions that are compatible with the Master Works™ resin systems.

The base colors allow a comprehensive range of colors to be formulated by color matching and blending.

The pigments used have been selected to provide excellent stability and light-fastness making them suitable for external use.

### FEATURES/BENEFITS

- Good pigment stability
- Excellent light-fastness
- Good pigment compatibility for blending
- Narrow base range allows virtually any color to be color matched
- Water based and environmentally friendly
- Low level of incorporation gives good color saturation.

### PROCESSING

Master Works™ pigment pastes should be added up to a maximum of 2% of the combined weight of the Component A and B mix.

The pigment should always be added to the A Component before mixing with the B Component. To ensure homogeneity the pigment should be mixed using a power drill with the Master Works™ high shear mixing blade attachment.

For small quantities hand mixing is acceptable. Care should be taken to check color matches from batch to batch of the Master Works™ resin system.

### APPLICATION AREAS

- Decorative surface finishing gelcoats for interior and exterior applications
- Pigmentation of positive spray systems
- Pigmentation of mass casting material
- Surface finishing techniques – see the Master Works™ Surface Finishing Manual

- Primary Yellow
- Primary Red
- Primary Blue
- Yellow Oxide
- Red Oxide
- Raw Umber

### PACKAGING

Standard pack size – one quart.  
5-gallon pails available on request



MASTERWORKS™ is a licensed trademark. These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our material and suggestions before adopting them on a commercial scale. Suggestions for uses of our products or the inclusion of descriptive material from patents and the citation of specific patents in this publication should not be understood as recommending the use of our products in violation of any patent or as permission or license to use any patents of PUMA Polymers.

V2-052909

**PUMA Polymers**

PO Box 5413, 2003 Curtain Pole Road, Chattanooga, TN 37406  
Toll Free: 877-744-0499 Telephone: 423-697-0499 Fax: 423-697-0437  
[www.pumapolymers.com](http://www.pumapolymers.com)